



WATERPROOFING MEANS PAZKAR

EPOXY PRIMER XL-100

A two-component water based epoxy primer.

Product Description

Epoxy primer XL-100 is an advanced ecologically friendly primer. The primer features excellent adhesion to Concrete, Bituminous membranes, wood, Polyurethane foam and asbestos. The primer has good chemical resistance and excellent durability.

Product Uses

Epoxy primer XL-100 serves as a priming layer above Concrete, Bituminous membranes, wood, Polyurethane foam and asbestos surfaces that are about to be coated.

Epoxy primer XL-100 serves as a priming layer for bridge deck waterproofing.

Technical properties

Color:	white
Specific gravity:	1.1±0.05 gr./cm ²
Coverage	100 g/m ² = 70 microns
Solid content	>60% (% wt)
Application Temperature	10-35°C
Mixing ratio	A=1; B=4
Pot life after mixing @ 25°C	1-2 hours
Dry to touch or before rain	4-6 hours
Dry to recoat	8-24 hours
Full chemical cure	7 days



WATERPROOFING MEANS PAZKAR

Instruction for use

- **Surface preparation**
All surfaces to which Epoxy primer XL-100 is applied must be sound, stable with an even finish and free from dirt, dust, loose debris, grease etc.
New Concrete must be at least 4 weeks old. Remove the laitance by light sand blasting cleaning or power grinding.
- **Primer preparation**
 - Insert content of component "A" to Component "B" container following 2 minutes of suitable mechanical stirring.
 - Dilution: To the homogenous material add 10 kg tap water and continue mixing for additional 2 minutes.
 - Holdup the mix material for 10 minutes and then mix for additional 2 minutes. The primer is ready for use.
- **Primer application**
Epoxy primer XL-100 may be applied by using a brush, roller or airless spray. Recommended quantity is 100-300 gr/m² according to surface properties. During application care should be taken to avoid excess material which can be recognize as a glossy layer over the surface.

Equipment care

Before Epoxy primer XL-100 has dried, clean tools using water.

Packaging

Epoxy primer XL-100 is available in the following packages:

- Component A – 2 kg.
- Component B – 8 kg.

Storage

- Store under cover out of direct sunlight and protect from extremes of temperature.
- In tropical climates the product must be stored in an air-conditioned environment.
- Shelf life is up to 12 months when stored as above.



Technical and application notes:

- We recommended to cover the primer not more than two days after application, in order to prevent dust accumulation.
- During mixing of the two components care should be taken in order ensure using the entire content of component "A".
- Mixing of the two components must be accomplished before diluting with water.
- The pot life of the primer is 4 hours @ 25°C.
- The component temperature during mixing should be 15-25°C.
- The primer is not flammable and free of organic solvents.

NOTE: Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.
For specific storage advice consult PAZKAR'S representatives.

For Safety detailed instructions please refer to Pazkar's safety sheets (MSDS).



Warranty

Pazkar's products are manufactured to rigid standards of quality. Pazkar makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Users must always refer to the most recent issue of the local product data publication for the product concerned. The user of the product must test the product's suitability for the intended application and purpose. Due to differences in materials, substrates and site conditions Pazkar assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including but not limited to, the implied warranty of merchantability, fitness for a particular purpose, nor any liability arising from any legal relationship. Subject to our terms and conditions, Pazkar grants a product warranty certificate for specific products, for any further information please contact us at info@pazkar.co.il. All orders are accepted subject to our current inventory, terms and conditions of sale and delivery.